(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 15 September 2005 (15.09.2005)

PCT

(10) International Publication Number WO 2005/084127 A2

(51) International Patent Classification: Not classified

(21) International Application Number:

PCT/IL2005/000254

(22) International Filing Date: 3 March 2005 (03.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/549,553 4 March 2004 (04.03.2004) US

(71) Applicants and

(72) Inventors: OREN, Ran [IL/IL]; Kibbutz Gaaton, 25130 Doar Na Oshrat (IL). MOOR, Dan [IL/IL]; Kibbutz Gaaton, 25130 Doar Na Oshrat (IL).

(74) Agent: G.E. EHRLICH (1995) LTD.; 11 Menachem Begin Street, 52 521 Ramat Gan (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SUTURE MANIPULATING AND CUTTING IMPLEMENT

(57) Abstract: An implement for manipulating a knotted suture during a surgical procedure, includes an elongated shaft having a proximal end engageable by the user for manipulating the instrument, and a distal end engageable with the knotted suture to be manipulated. The distal end of the elongated shaft has an end face formed with a recess for receiving the knot of the suture. The distal end of the elongated shaft is formed with an open slot starting from a location spaced from the end face and leading to the recess in the end face, such as to enable the knotted suture to be introduced into the slot and the recess by effecting a sidewise movement. The implement further includes a tubular cutter member enclosing the elongated shaft and formed with an annular cutting edge engageable with a suture in the open slot of the shaft upon movement of the elongated shaft with respect to the tubular cutter member, or by vice-versa.



